

Seat Belts for Forklift

Forklift Seat Belts - Described in the Regulation guidelines are the application of seatbelts and operator restraints on forklifts. It states that the responsibility falls on the employers' to ensure that each and every machinery, piece of equipment and tool is utilized correctly used in accordance to the instructions of the maker.

Rough Terrain forklifts ought to meet the guidelines of ANSI Standard ASME B56.6-1992 regarding their inspection, fabrication, use, design and maintenance.

Mobile machines such as side boom tractors together with a Rollover Protective Structure (ROPS), need to include seat belts which meet the Society of Automotive Engineers safety requirements; Society of Automotive Engineers Standard J386 JUN93, Operator Restraint System for Off-Road Work Machines. If any mobile machinery has seat belts required by law, the driver and subsequent passengers need to ensure they utilize the belts each time the motor vehicle is in motion or engaged in operation as this could cause the equipment to become unsteady and hence, unsafe.

If a seat belt or various driver restraint is required on a forklift.

The seat belt requirements while working a lift truck depend on various factors. Whether the forklift is equipped along with a Rollover Protective Structure, the kind of forklift itself and the year the forklift was actually manufactured all add to this determination. The manufacturer's directions and the requirements of the applicable standard are referenced in the Regulation.

Referring to an operator restraint device, system or enclosure, ANSI Standard ASME B56.1-1993 in the case of powered industrial trucks, is designed to be able to help the operator in reducing the chance of entrapment of the head and/or torso between the truck and the ground in the event of a tip over. The system or restraint device might consist of a seat belt, although a seat belt is not necessarily a part of such device or system.